

Applicants : Niall R. Lynam et al.
Page : 8

IN THE CLAIMS:

Please cancel Claims 1-59. Please add the following new Claims:

1-59. (cancelled)

60. (new) An automobile exterior sideview mirror system comprising:
an exterior sideview mirror assembly adapted for attachment to a side of an automobile;
said exterior sideview mirror assembly including a reflective element assembly;
said reflective element assembly including a first reflective element having unit magnification and a second reflective element having a curvature;
said first reflective element and said second reflective element supported at a support element;
said second reflective element disposed at an outer, upper portion of said reflective element assembly when said reflective element assembly is included in said exterior sideview mirror assembly and when said exterior sideview mirror assembly is attached to the side of an automobile;
said second reflective element supported on said support element adjacent to and separate from said first reflective element;
a demarcation element between said first reflective element and said second reflective element; and
wherein the portion of said second reflective element adjacent said demarcation element has a front surface generally coplanar with the front surface of said first reflective element.

61. (new) The exterior sideview mirror system of Claim 60, wherein said demarcation element is dark colored.

Applicants : Niall R. Lynam et al.
Page : 9

62. (new) The exterior sideview mirror system of Claim 60, wherein said reflective element assembly includes a first bezel portion extending around said first reflective element, said demarcation element comprising a segment of said first bezel portion.

63. (new) The exterior sideview mirror system of Claim 60, wherein said second reflective element comprises a curved reflective element comprising a bent substrate with at least one radius of curvature in the range of about 4000 mm to about 100 mm.

64. (new) The exterior sideview mirror system of Claim 60, wherein said support element comprises a frame, said first and second reflective elements being mounted at said frame.

65. (new) The exterior sideview mirror system of Claim 64, wherein said second reflective element is mounted at said frame at an outboard position, and said first reflective element is positioned adjacent said second reflective element and at an inboard position with respect to said second reflective element when said exterior sideview mirror assembly is mounted to an automobile.

66. (new) The exterior sideview mirror system of Claim 64, wherein said first reflective element is mounted at said frame by a backing plate.

67. (new) The exterior sideview mirror system of Claim 66, wherein said backing plate is adapted to mount to an actuator operable to adjust the orientation of said reflective element assembly.

68. (new) The exterior sideview mirror system of Claim 67, wherein said actuator comprises an electrical actuator.

69. (new) The exterior sideview mirror system of Claim 64, wherein said first reflective element and said second reflective element are adjacently attached at said frame, said frame including a first perimeter portion and a second perimeter portion, said first perimeter portion

Applicants : Niall R. Lynam et al.
Page : 10

extending around said first reflective element, and said second perimeter portion extending around said second reflective element.

70. (new) The exterior sideview mirror system of Claim 69, wherein a side portion of said first perimeter portion of said frame provides said demarcation element between said first reflective element and said second reflective element.

71. (new) The exterior sideview mirror system of Claim 69, wherein said second perimeter portion is angled downwardly and forwardly with respect to said first perimeter portion when said mirror assembly is mounted to an automobile.

72. (new) The exterior sideview mirror system of Claim 64, wherein said second reflective element is attached at said frame by at least one of an adhesive attachment and a mechanical attachment.

73. (new) The exterior sideview mirror system of Claim 66, wherein said backing plate is attached to one side of said first reflective element and said frame by one of an adhesive attachment, a welded attachment, and a mechanical attachment.

74. (new) The exterior sideview mirror system of Claim 73, wherein an opposed side of said frame forms a bezel around said first reflective element.

75. (new) The exterior sideview mirror system of Claim 60, wherein said first reflective element includes a rearward field of view having a principal axis different from a principal axis of the rearward field of view of said second reflective element when mounted in said exterior sideview mirror assembly.

76. (new) The exterior sideview mirror system of Claim 75, wherein said principal axis of the rearward field of view of said second reflective element is directed generally outwardly and downwardly with respect to a longitudinal axis of the automobile.

Applicants : Niall R. Lynam et al.
Page : 11

77. (new) The exterior sideview mirror system of Claim 76, wherein said principal axis of the rearward field of said second reflective element forms a downward angle with respect to the longitudinal axis of the automobile in the range from about 0.75° to about 5° .

78. (new) The exterior sideview mirror system of Claim 77, wherein said downward angle is in a range from about 1.5° to about 3.5° .

79. (new) The exterior sideview mirror system of Claim 77, wherein said downward angle is in a range of about 2° to about 3° .

80. (new) The exterior sideview mirror system of Claim 76, wherein said principal axis of said second reflective element forms an outward angle with respect to the longitudinal axis of the automobile in a range of about 0.75° to about 5° .

81. (new) The exterior sideview mirror system of Claim 80, wherein said outward angle is in a range of about 1° to about 3° .

82. (new) The exterior sideview mirror system of Claim 81, wherein said outward angle is in a range of about 1.25° to about 2.5° .

83. (new) The exterior sideview mirror system of Claim 81, wherein said exterior sideview mirror assembly comprises a fixedly attached exterior sideview mirror assembly.

84. (new) The exterior sideview mirror system of Claim 60, wherein said exterior sideview mirror assembly comprises a break-away exterior sideview mirror assembly.

85. (new) The exterior sideview mirror system of Claim 60, wherein said exterior sideview mirror assembly comprises a powerfold exterior sideview mirror assembly.

Applicants : Niall R. Lynam et al.
Page : 12

86. (new) The exterior sideview mirror system of Claim 60, wherein at least one of said first reflective element and said second reflective element comprises a variable reflectance reflective element.

87. (new) The exterior sideview mirror system of Claim 86, wherein each of said first reflective element and said second reflective element comprises a variable reflectance reflective element.

88. (new) The exterior sideview mirror system of Claim 60, wherein said first reflective element comprises an electrochromic reflective element.

89. (new) The exterior sideview mirror system of Claim 60, wherein said first reflective element has a first principal axis and said second reflective element has a second principal axis when supported on said support element, said second principal axis being angled outwardly from said first principal axis at an angle in a range of about 0.75° to about 5° .

90. (new) The exterior sideview mirror system of Claim 89, wherein said second principal axis is angled outwardly from said first principal axis at an angle in a range of about 1° to about 3° .

91. (new) The exterior sideview mirror system of Claim 89, wherein said second principal axis is angled outwardly from said first principal axis at an angle in a range of about 1.25° to about 2.5° .

92. (new) The exterior sideview mirror system of Claim 60, wherein said second reflective element has a second principal axis that is angled downwardly from a first principal axis of said first reflective element when supported on said support element.

93. (new) The exterior sideview mirror system of Claim 92, wherein said second principal axis is angled downwardly from said first principal axis at an angle in a range of approximately 0.75° to about 5° .

94. (new) The exterior sideview mirror system of Claim 92, wherein said second principal axis is angled downwardly from said first principal axis at an angle in a range of about 2° to about 3°.

95. (new) The exterior sideview mirror system of Claim 60, wherein said second reflective element has a second principal axis that is directed generally outwardly and downwardly with respect to a longitudinal axis of an automobile when said mirror assembly is mounted to the automobile.

96. (new) The exterior sideview mirror system of Claim 60, wherein said support element includes a support surface for said second reflective element, said support surface angling a second principal axis of said second reflective element.

97. (new) An automobile exterior sideview mirror system comprising:
an exterior sideview mirror assembly adapted for attachment to a side of an automobile;
said exterior sideview mirror assembly including a reflective element assembly;
said reflective element assembly including a first reflective element having unit magnification and a second reflective element having a curvature;
said second reflective element disposed at an outer, upper portion of said reflective element assembly when said reflective element assembly is included in said exterior sideview mirror assembly and when said exterior sideview mirror assembly is attached to the side of an automobile;
said second reflective element disposed adjacent to and separate from said first reflective element;
said first reflective element including a rearward field of view having a principal axis different from a principal axis of the rearward field of view of said second reflective element when mounted in said exterior sideview mirror assembly;

Applicants : Niall R. Lynam et al.
Page : 14

a demarcation element between said first reflective element and said second reflective element; and

wherein the portion of said second reflective element adjacent said demarcation element has a front surface generally coplanar with the front surface of said first reflective element.

98. (new) The exterior sideview mirror system of Claim 97, wherein said reflective element assembly includes a first bezel portion extending around said first reflective element, said demarcation element comprising a segment of said first bezel portion.

99. (new) The exterior sideview mirror system of Claim 97, wherein said second reflective element comprises a curved reflective element comprising a bent substrate with at least one radius of curvature in the range of about 4000 mm to about 100 mm.

100. (new) The exterior sideview mirror system of Claim 97, further comprising a support element, said first reflective element and said second reflective element supported at said support element.

101. (new) The exterior sideview mirror system of Claim 100, wherein said support element including a support surface for said second reflective element, said support surface angling said principal axis of said second reflective element.

102. (new) The exterior sideview mirror system of Claim 101, wherein said principal axis of said second reflective element is directed generally outwardly and downwardly with respect to the longitudinal axis of an automobile when said mirror assembly is mounted to the automobile.

103. (new) The exterior sideview mirror system of Claim 97, further comprising an actuator operable to adjust the orientation of said reflective element assembly.

104. (new) The exterior sideview mirror system of Claim 97, wherein said principal axis of the rearward field of view of said second reflective element is directed generally outwardly and downwardly with respect to a longitudinal axis of the automobile.

105. (new) The exterior sideview mirror system of Claim 97, wherein said principal axis of said second reflective element forms an outward angle with respect to a longitudinal axis of the automobile.

106. (new) The exterior sideview mirror system of Claim 97, further comprising a frame, said first and second reflective elements being mounted at said frame, said frame including a first perimeter portion and a second perimeter portion, said first perimeter portion extending around said first reflective element, and said second perimeter portion extending around said second reflective element.

107. (new) The exterior sideview mirror system of Claim 106, wherein a side portion of said first perimeter portion of said frame provides said demarcation element between said first reflective element and said second reflective element.

108. (new) An automobile exterior sideview mirror system comprising:
an exterior sideview mirror assembly adapted for attachment to a side of an automobile;

said exterior sideview mirror assembly including a reflective element assembly;

said reflective element assembly including a first reflective element having unit magnification and a second reflective element having a curvature;

an actuator operable to adjust the orientation of said reflective element assembly;

said second reflective element disposed at an outer, upper portion of said reflective element assembly when said reflective element assembly is included in said exterior sideview mirror assembly and when said exterior sideview mirror assembly is attached to the side of an automobile;

said second reflective element disposed adjacent to and separate from said first reflective element;

a demarcation element between said first reflective element and said second reflective element; and

wherein the portion of said second reflective element adjacent said demarcation element has a front surface generally coplanar with the front surface of said first reflective element.

109. (new) The exterior sideview mirror system of Claim 108, wherein said first reflective element has a first principal axis and said second reflective element has a second principal axis, said second principal axis being angled outwardly from said first principal axis.

110. (new) The exterior sideview mirror system of Claim 109, wherein said second principal axis is angled downwardly from said first principal axis of said first reflective element.

111. (new) The exterior sideview mirror system of Claim 110, wherein said second principal axis is directed generally outwardly and downwardly with respect to a longitudinal axis of an automobile when said mirror assembly is mounted to the automobile.

112. (new) The exterior sideview mirror system of Claim 110, further comprising a support element, said support element including a support surface for said second reflective element, said support surface angling said second principal axis of said second reflective element relative to said first principal axis.

113. (new) The exterior sideview mirror system of Claim 112, wherein said support element comprises a frame, said first and second reflective elements being mounted at said frame.

114. (new) The exterior sideview mirror system of Claim 113, wherein said second reflective element is mounted at said frame at an outboard position, and said first reflective

Applicants : Niall R. Lynam et al.
Page : 17

element is positioned adjacent said second reflective element and at an inboard position with respect to said second reflective element when said exterior sideview mirror assembly is mounted to an automobile.

115. (new) The exterior sideview mirror system of Claim 114, wherein said frame includes a first perimeter portion and a second perimeter portion, said first perimeter portion extending around said first reflective element, and said second perimeter portion extending around said second reflective element.

116. (new) The exterior sideview mirror system of Claim 115, wherein a side portion of said first perimeter portion of said frame provides said demarcation element between said first reflective element and said second reflective element.

117. (new) The exterior sideview mirror system of Claim 116, wherein said second perimeter portion is angled downwardly and forwardly with respect to said first perimeter portion when said mirror assembly is mounted to an automobile.